



# EXTERIOR

- Long-lasting protection under severe climate
- Excellent water & oil resistance
- Excellent mold & fungus resistance
- Excellent dirt pick-up resistance
- Low VOCs



# INTERIOR

- 99.99% anti-bacteria with Nano Silver (Ag+)
- Excellent washability
- Silky Smooth Finishing
- Excellent coverage & hiding
- Low VOCs & odor

# **Hybrid Nano**














The term 'Hybrid' has widely known for a thing made by combining 2 different elements. TOA Research & Development Team has developed the latest innovative paint technology from Germany: Protective Hybrid Technology.

We combine 2 imported premium quality nanomolecules from the U.S. and Germany into one pail of paint to assure it has the excellent protective property, deep into molecular surface level.







Surface Level of Paint

# **How Hybrid Technology works:**

# Nano Silicone: Water-Repellent

Did you know water is a cause of paint problems? Nano Silicone is an inorganic substance able to repel water molecule out of paint film.

Without water penetration, it protects surfaces from problems: chalking, blistering, algae-fungus formation, and dull colors. Plus, Nano Silicone has another special property to resist UV light from the sun for over years.

# Nano Fluorocarbon: Oil-Repellent

Dirt and oil from pollution and rain make house look old and lousy. Nano Fluorocabon has exclusive properties of excellent dirt-stain repellent and oil resistance. Paint film becomes excellently washable, highly protective, and self-cleaning over time.

From these facts, you can now be confident that TOA NanoShield is the best and smart choice that is worth the investment.



TOA Nanoshield Paint



# Long-lasting protection under severe climate

TOA NanoShield has superior efficiency of UV protection and durable under severe climate conditions, up to 8 years.



# Water & Oil Resistance

TOA NanoShield is resistant to water because of containing Nano Silicone molecules. Paint films will not absorb water molecules. Stains from rains will be washed off through paint films.



# **Excellent Dirt Pick-up Resistance**

TOA NanoShield has slippery surface properties. Water or oil stains will not be easily stick on paint film.



# Excellent on Mold & Fungus Resistance

TOA NanoShield prevent paint film from peeling off and mold and fungus formation. Paint film will be new and durable over years.

# TOA Nano Hybrid Nano







Low V@C Low@ Odour



**INTERIOR** 

The term 'Hybrid' has widely known for a thing made by combining 2 different elements. TOA Research & Development Team has developed the latest innovative paint technology from Germany: *Protective Hybrid Technology*.

We combine 2 imported premium quality nanomolecules from the U.S. and Germany into one pail of paint to assure it has the excellent protective property, deep into molecular surface level.

# Nano Nano

# Nano Silver: 99.9% Anti-bacteria

You may not be aware that bacteria around you is more dangerous than you think. Bacteria is one of the causes of many common diseases around you, such as, severe diarrhea, minor skin infection, and high fever.

Nano Silver is a substance that has been tested and proved by renown laboratories.


Nano Silver has a unique property to stop the growth of bacteria up to 99.9%.

# Nano Fluorocarbon: Excellent Washability

Nano Fluorocarbon provides a stronger protective paint film than common washable interior paints. The nanomolecule can repel, both water and oil. As a result, any stain and dirt can be easily removed out from the surface, with its excellent washability and durability property.

Moreover, **TOA NanoClean** is low odor and low VOCs (Volatile Organic Compounds). From these facts, you can now be assured that **TOA NanoClean** is the best and wise choice for your house and beloved family.

# How Nano Silver Ion (Ag+) works:







Normal Paint : Bacteria grows



TOA NanoClean : Bacteria stops growing

# 99.9% Anti-bacteria with Nano Silver

TOA NanoClean is able to kill 99.99% of bacteria with Nano Silver (Ag+) that is widely used in premium air conditions and refrigerators.

Nano

Anti-Bacteria



# Excellent Coverage & Hiding

TOA NanoClean has superior coverage and hiding power with smooth and silky finishing.



# Excellent Washability with Silky Smooth Finishing

TOA NanoClean has the excellent washable property and assures that walls will look clean and new at all time.



# Protective against Fungus & Mold Formation

TOA NanoClean has the excellent fungus and mold resistance that protects unwanted molecules on paint films from years to years.

# Safe for Users & Environments

It is lead-free and mercury-free, with low odor and low VOCs technology. Nano Series is a green product that is environmental-friendly.












100% Premium Acrylic Emulsion Paint For Exterior & Interior


# **Exterior Guide**


Trendy color matching for outstanding & unique exterior

# Classic Style









# Classic Style



# Contemporary Style.



- Available in 1 Litre, 5 Litres, and 15 Litres
- Available in White 1100 for NanoShield & 2100 for NanoClean


# Interior Guide

Harmonized color matching for elegant & modern interior decoration with your own style

# Color Matching Advice

60% Light Tone : Major Wall







Feature Wall 1

30% Outstanding Tone: Outstanding Tone: Feature Wall 2




# Romantic Style,





# Cozy Style





# EXTERIOR

- Long-lasting protection under severe climate
- Excellent water & oil resistance
- Excellent mold & fungus resistance
- Excellent dirt pick-up resistance
- Low VOCs



# INTERIOR

- 99.99% anti-bacteria with Nano Silver (Ag+)
- Excellent washability
- Silky Smooth Finishing
- Excellent coverage & hiding
- Low VOCs & odor

### Penyediaan Permukaan

Pastikan permukaan yang hendak dicat bersih, kering dan bebas daripada kekotoran, minyak, dan sebagainya. Tanggalkan semua cat yang menggelupas atau sisa berserbuk secara memberus dengan memberus dengan berus keras sambil menyembur air atau menggunakan penyembur air tekanan tinggi.

Permukaan yang dicemari cendawan, likan, alga atau lumut mesti dibersihkan dengan TOA MicroKill. Baiki kecacatan dengan TOA Acylic Filer atau TOA 102 D-Cote. Mengunakan TOA Wallsila 800/ TOA Wallsila 900 jika terdapat alkali tinggi dipermukaan. Tidak sesuai menyapu cat pada dinding yang mempunyai kelembapan tinggi, ketika hujan dan permukaan berserbuk.

# Data Penggunaan

Kering Disentuh

Tempoh Lapisan Semula Jumlah Lapisan

: 30 minit, bergantung pada suhu dan

kelembapan 1 - 2 Jam

10 -12 m² per litre per lapisan minimum 2 lapisan

Guna air bersih (Jika perlu, cairkan

dengan maksima 10% air)

## 表面处理

确保被涂装的表面清洁,干燥,无油脂或者其他污渍。请使 用硬质刷子或高压喷水器将墙面的松散或剥落物质清除干净 若墙面生长有霉菌或者藻类生物,请使用TOA MicroKill进行 祛除处理。请使用TOA Acrylic Filler修补墙面裂纹,或使用 TOA 102 D-Cote抚平墙面。若墙体碱性较高,应使用TOA Wallsila 800 / TOA Wallsila 900 底漆为 墙壁做封底处理。 请勿在水分含量较高的墙面和潮湿下雨的 天气情况下施工, 并且勿直接在墙灰的粉状表面上涂装。

## Surface Preparation

Ensure the surface is clean, dry, free from dirt, oil, grease and other foreign bodies. Remove all loose or powdery residues by brushing, scraping or high pressure water jet. Areas affected by mould, lichen, algae or moss must be treated with TOA MicroKill. Repair wall cracks with TOA Acrylic Filler or smoothen wall with TOA 102 D-Cote. Apply TOA Wallsila 800 / TOA Wallsila 900 where high alkalinity is present

**DO NOT** apply where moisture content is high or during rainny weather, or powdery surface.

### 施工细则

30分钟 再次涂刷间隔 1-2小时

理论可覆盖面积 10-12平方米/公升, 视墙面情况而定

涂刷层数 至少2层

产品无需稀释,若有必要,至多加入

10%的清水

### **Application Details**

Thinning

Touch Dry 30 minutes, depending on ambient temperature

Recoat Interval

1 to 2 hours 10 to 12 m²/litre, depending on substrate condition Theoretical Coverage No. of Coats

Thinning is not required, if necessary, thin up to

maximum of 10% water

### Maklumat Keselamatan. Kesihatan dan Alam Sekitar

Pastikan tin sentiasa ditutup rapat dan jauhkan dari kanak-kanak. Jauhkan dari suhu yang keterlaluan dan simpan di tempat yang teduh. Permakaian pelindung mata yang sesuai adalah disyorkan apabila mengecat. Jika berkena pada mata, basuh dengan air bersih dan dapatkan rawatan perubatan dengan segera. Bersihkan percikan cat di kulit, gunakan pembersih kulit yang sesual atau sabun serta air. Jangan buang sisa cat ke dalam longkang atau saliran air. Rujuk kepada Lembaran Data Perkhidmatan Teknikal TOA Paint untuk maklumat yang lebih lanjut.

密封常温保存且远离儿童。涂漆时必须配戴护目镜,若意外接触 眼睛,须立即用大量清水冲洗眼部,并立刻寻求医疗救护。若接 触皮肤,请配合使用肥皂或其他安全的洁肤产品进行冲洗即可。 若漆桶意外翻倒泼洒,请用泥土或干沙覆盖后清除。请勿把产品 傾倒或丢弃在河道或水源里。产品详细数据请查阅TOA Paint技

Keep container closed when not in use and out of reach of children. Protect from extremes of temperature. Store in a cool place. Avoid contact with skin and eyes. It is advisable to wear protector while applying. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. To remove splashes of paint from the skin, use soap and water or skin care product. Do not empty paint into drains or water courses. Refer to TOA Paint Technical Service Date Sheet for further details.

# Painting System

## **Surface Preparation**

# **Primer**

# **Top Coat**



Construction Chemicals Note: Please refer to its catalog





Coat of TOA Wallsila 800 for new surface or 1 Coat of TOA Wallsila 900 for old surface





2 coats of TOA NanoShield or TOA NanoClean





TOA Color World, Experience color selection with our computerized color tinting machine at TOA's dealers near your house.

Convenient: Choose any colors you want from TOA's fandeck Time-Saving: High tinting accuracy, within only 3 minutes.

Quality: The same assured quality as paints produced from factory standard





TOA Paint Product Sdn. Bhd.

Lot 63802, Jalan Telok Gong, 42000, Port Klang, Selangor, Malaysia

Tel: +603 3134 1629 / 3134 1639 Fax: +603 3134 1581 Email: toa@toagroup.com.my Website: www.toagroup.com.my



Application System