



PAINT

We Paint Happiness 😊

Captain GLOSS

HIGH GLOSS ENAMEL FOR EXTERIOR & INTERIOR



6 NEW COLOURS!!



Hot Tone



Maroon C024



Chilli C699



Signal Red C613



Sunrise C004



Smooth Tone



Chrome Yellow **NEW!** C400



Skim C052




Ivory C831



Sunrise Yellow C669



Cheju Yellow C622



Lilly C146


Go-Green Tone




Bottle Green C074



Grass Green C639



Apple Green C638



Pangkor **NEW!** C413



Kiwi Parrot C668



*Available in White (C145), Black (C144), and Aluminium (C698)

*The colors presented are as close as the actual production as modern printing techniques allow.

Ocean Tone



Wira Blue C227




Marine Blue **NEW!** C649



Neptune C631



Celebration **NEW!** C504



Mistral C033

Wood Tone



Leather C039



Deep Leather C045



Mocha Latte **NEW!** C102



Golden Brown C044



Golden Honey C627

Grey Tone



Steel Grey C097




Algerian Mist **NEW!** C744



Executive Grey C604



Smoke Grey C095



Venus C406



Primer



Red Oxide Primer



Grey Oxide Primer



Captain GLOSS

HIGH GLOSS ENAMEL FOR EXTERIOR & INTERIOR



Available in 1Liter & 5Liter

Captain Gloss is a quality alkyd gloss enamel, specially developed to endure the most severe climate. It is made of high quality alkyd resin and has high toughness pigments. This enamel has excellent high gloss effect and levelling, provides smooth and mirror like finishing with good hiding properties. It is suitable for use on wood or metal surfaces and can be used for both exterior and interior.

Surface Preparation

Use suitable sandpaper to smoothen uneven surfaces, rust, defective or poorly adhere paint film, dirt, grease or wax. Apply one coat of **Captain Grey Green Primer** or **Captain Red Oxide Primer** then follow by two coats of **Captain Gloss**. New galvanized metal, aluminium, stainless steel or alloy surfaces need to be degreased and apply one coat of **TOA Multiprime**.

Touch Dry : Less than 1 hour

Recoat : 3-4 hours

Film Properties : Approx. 40 microns per coat (Do not apply too thick in a single coat, better split into more layers)

Theoretical Coverage: 10-12 m² / liter

No. of coat : 2 coats

Application : Brush, roller, air spray, or airless spray

Thinning : For normal use, thinning is not necessary. Use thinner for dilution if necessary.

Cleaning up: Clean all paint equipments with thinner for dilution immediately after using

Safety, Health & Environment

- FLAMMABLE. During painting, make sure no source of ignition at surrounding and no smoking.
- When not in use, store paint in a cool and under shaded place and not directly exposed to the sunlight.
- Provide proper ventilation and wear a mask during painting. Do not breathe vapour or spray.
- Keep doors and windows open during application and drying.
- It is advised to wear an eye protection. If the eye in contact with the paint, rinse with plenty of clean water and seek medical treatment immediately.
- To remove splashes of paint from the skin, use suitable cleanser soap and water.
- Do not dispose any paint into drains or water courses.

Captain Gloss 是一种优质醇酸光泽瓷漆，专为承受最恶劣的气候而开发。它由优质醇酸树脂制成，并具有高韧性颜料。这种瓷漆具有优异的高光泽效果和流平性，提供光滑和镜面般的饰面，具有良好的遮盖性能。它适用于木材或金属表面，可用于外部和内部。

表面处理

使用适合的砂纸打磨不平整的表面，生锈、有缺陷或附着不良的漆膜、污垢、油脂或蜡，涂上一层**Captain Grey Green Primer**或**Captain Red Oxide Primer**，然后涂上两层**Captain Gloss**。新的镀锌金属、铝、不锈钢或合金表面需要脱脂并涂上一层**TOA Multiprime**。

漆干 : 1 小时内

重涂时间 : 3 - 4 小时

厚度 : 每层接近40微米 (每层别涂太厚，分多次上漆)

理论覆盖面积 : 每公升 10 - 12 平方米

涂层次数 : 2 层

涂刷工具 : 漆刷、滚轴、有风喷漆枪或无风喷漆枪

调稀 : 通常不必调稀，如有需要，使用调稀水 (Thinner)

清洗 : 完工后请即刻以Thinner立即清洗所有工具。

安全、健康及环保细则

易燃，远离火源。绝对吸烟，存于阴凉干爽处。漆桶必须盖紧和直立放置。在空气流通处上漆及戴上口罩，别吸进漆雾。上漆时则戴上护眼镜，万一不小心被漆油触及眼睛，立刻用清水清洗，同时去看医生。若溅到皮肤，可用适当的洁肤品或香皂和清水清洗。不可丢弃在水沟或水道里。

Captain Gloss adalah cat kilat alkyd berkualiti yang telah dirumus khas untuk tahan lasak terhadap cuaca tropika. Ianya diperbuat daripada alkyd resin yang berkualiti tinggi dan mempunyai pigmen tahan lasak. Enamel ini mempunyai kilauan yang tinggi dan permukaan yang licin seperti cermin dengan daya penutupan yang baik. Ianya sesuai digunakan pada permukaan kayu dan besi sama ada di luar atau di dalam bangunan.

Penyediaan permukaan:

Semua permukaan karat, bahan cat yang mengelupas, kekotoran, gris atau lilin mesti digosok dengan kertas pasir sehingga licin serta bersih dari debu dan habuk. Sapu selapis **Captain Grey Green Primer** atau **Captain Red Oxide Primer** untuk permukaan besi. Diikuti oleh dua lapisan **Captain Gloss**. Bahan-bahan galvani, aluminium, keluli tahan karat dan aloi, permukaannya mestilah dibersihkan diikuti dengan satu lapisan **TOA Multiprime**.

Kering Sentuh : kurang daripada 1 jam

Ulang Cat : 3 - 4 jam

Ciri lapisan : lebih kurang 40 micron selapis (jangan sapu terlalu tebal dalam satu lapis)

Purata Liputan : 10 - 12 m² / liter

Bilangan Lapisan : 2 lapis

Cara Mengguna : Berus, alat penggelek, alat penyembur cat

Pencairan : Untuk kegunaan biasa, pencairan tidak diperlukan, jika perlu, gunalah thinner untuk pencairan

Pembersihan : Cuci semua alat perkakas dengan thinner sebaik sahaja kerja-kerja mengecat selesai dilakukan.

Maklumat Keselamatan, Kesihatan dan Persekitaran

MUDAH TERBAKAR. Jauhkan daripada punca api, jangan merokok. Jika tidak digunakan simpanlah tin di tempat teduh dan tertutup rapat. Jangan dedahkan tin kepada cahaya matahari. Pastikan aliran udara sempurna semasa cat disapu. Jangan hidu wap atau semburannya. Pintu dan tingkap mestilah sentiasa buka semasa menyapu dan mengeringkan cat. Adalah digalakkan memakai cermin perlindungan mata. Jika terkena pada mata, segera basuh dengan air dan dapatkan rawatan perubatan. Bersihkan percikan cat daripada kulit, gunakan pembersih kulit yang sesuai atau sabun serta air. Jangan buang sisa cat ke dalam longkang atau saluran air.

Recommended Painting System – Metal Surface

Primer	Undercoat	Top coat
1 Coat of Captain Red Oxide Primer or Captain Grey Green Primer (For New & Old Surfaces)	1 Coat of Captain Undercoat	2 Coat of Captain Gloss

Recommended Painting System – Wood Surface

Undercoat	Top coat
1 Coat of Captain Undercoat	2 Coat of Captain Gloss



We Paint Happiness

TOA Paint Products Sdn. Bhd. (Factory) (647481-P)

Address: Lot 63802, Jalan Telok Gong, Telok Gong, 42000 Port Klang, Selangor, Malaysia.

Phone Number: +603 3134 1629 Customer Hotline: +603 7725 2699



TOA Paint Products



@toapaintmy

www.toagroup.com.my