

# **ROAD LINE PAINT**

# **Abrasion Resistant Road Marking**

**TOA ROAD LINE PAINT** is a high performance alkyd modified reflective and non-reflective road marking paint with excellent durability and obliterating power.

Recommended Use: ROAD LINE PAINT is used as self priming and finishing coat for bitumen

or asphalt surfaces. It is suitable for both interior and exterior uses such as car park marking, directional arrow marking, lot numbering, divider line

marking, etc.

#### **Technical Information**

Finish Matt

Vehicle type Solvent based

Colour White, Black & Yellow

(Reflective & Non-Reflective)

Volume Solids Approx. 50% (nominal)

Flash Pont 35°C

Specific Gravity 1.47 – 1.52 (Depends on color)

Viscosity 70-90 KU

Chemical Resistance Not recommended if spillage of solvent is likely

Water Resistance Good
Shelf Life 24 months

## **Application Details**

Application methods Brush or roller

Mixing Ratio (by volume) The paint is ready for use after thorough stirring.

For conventional air spray, 30% thinning is

recommended

Pot Life NA (single pack)
Thinner / Cleaner Pegasol / Solvesso
Dry to Touch 20 to 30 minutes

Dry to Overcoat 1 hour (maximum indefinite)

 $\begin{array}{ll} \mbox{Practical Spreading Rate} & 8-9 \ m^2/ \ \mbox{Litre} \\ \mbox{Recommended Dry Film Thickness (dft)} & 50-60 \mu \end{array}$ 

#### **Technical Data Sheet - ROAD LINE PAINT**

## **Surface Preparation**

Surface must be sound, clean, dry and free from all defective or poor adhering dirt. Rubbish, dust, sand, etc

# **Typical Painting System**

Substrate Primer Finishing Coat (2 coats)
---

Bitumen or Asphalt Not Required TOA ROAD LINE PAINT

## **Storage & Packaging**

Storage The product must be kept in a cool and well

ventilated place protected from direct sunlight

Container must be tightly sealed

Handling Handle with care. Stir well before use

Packing size 5 Litres

## **Safety Precaution**

This product is flammable; keep away from the sources of ignition and do not smoke.

Avoid contact with skin and eyes. It is advisable to wear eye protection while painting. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Keep container closed when not in use. Provide good ventilation during application.

Do not empty into drains or water sources.

#### Keep out of reach of Children.

**Disclaimer:** The above information is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given information without prior notice.

TOA PAINT PRODUCTS SDN. BHD